

CE
ISO9001:2008

JAL Series

1000~5000 Lubricator



JAL2000



JAL4000

FRL

JC

FE

GC

ZYR10

MAR300LK

AC, BC

AFC, BFC

AF, BF

AR, BR

AFR, BFR

AL, BL

JAC

JAF

JAR



JAW

JAL


PTH

JAD

Ordering Code

| JA | L | 4000 | 04 | N |
|--|------------|---------------|--------------|---------------------------------|
| Series | Function | Specification | Port size | Wiring Form |
| JAL2000-02 | Lubricator | 1000 | M5: M5 x 0.8 | Blank: Standard N: Metal cup |
|  JAL3000-03  | | 2000 | 01: G1/8" | |
| | | 3000 | 02: G1/4" | |
| | | 4000 | 03: G3/8" | |
| | | 5000 | 04: G1/2" | |
| | | | 06: G3/4" | |
| | | | 10: G1" | |

Symbol



Specification

| Model | JAL1000-M5 | JAL2000-01 | JAL2000-02 | JAL3000-02 | JAL3000-03 | JAL4000-03 | JAL4000-04 | JAL4000-06 | JAL5000-06 | JAL5000-10 |
|-----------------------------|----------------|------------|------------|------------|------------|----------------|------------|------------|------------|------------|
| Rated Flow | 95 | 800 | 800 | 1700 | 1700 | 5000 | 5000 | 6300 | 7000 | 7000 |
| Port Size | M5 | 1/8 | 1/4 | 1/4 | 3/8 | 3/8 | 1/2 | 3/4 | 3/4 | 1 |
| Max. Adjustable Pressure | | | | | | 1.0 MPa | | | | |
| Proof Pressure Resistance | | | | | | 1.5 MPa | | | | |
| Operating Temperature Range | | | | | | 5 ~ 60 °C | | | | |
| Recommended Lubricant | 0.05 ~ 0.7 MPa | | ISO VG 32 | | | | | | | |
| Container Material | | | | | | Poly Carbonate | | | | |
| Container Cup | Not Available | | | Iron | | | | | | |